
Configurable optical cryostat for demanding applications in quantum



Key features


- >250mW Cooling at 4.2 Kelvin
- Low temperature and vibrations
- Cryogen-free/closed-cycle cryostat
- Turn-key equipment solution with push button cooling
- External control via ethernet
- Free-space optical access
- Multiple vacuum feedthroughs for RF, DC, and Fiber Cables

Optical Cryostat with High Cooling Capacity and Large Configurable Sample Space

High cooling capacity with large configurable sample space allows a user to easily design any experiment in

the Cryostation 200 PT. The closed-cycle optical cryostat utilizes a pulse tube cryocooler and Montana Instruments patented low vibration technology to provide users superior mechanical and electrical vibrations. Six customizable vacuum- feedthroughs and >20 watts of cooling on the first stage of the sample platform allows for up to 100 RF feedthroughs or DC connections. Montana Instruments Galaxy Software provides push button cooldown/heat up control of your optical cryostat and advance remote monitoring, control and analysis of your system.

Cold science made **simple**




Quantum Design GmbH

Breitwieserweg 9

D-64319 Pfungstadt

www.qd-europe.com

Configurable optical cryostat for demanding applications in quantum



Sample Platform

The 200mm 4K low vibration breadboard platform offers maximum flexibility in design of your experiment. Eight optical windows allow for transmission or reflective measurements. Unparalleled optical access to your sample can be achieved by either low working distance windows or a Cryo-Optic that integrates a high NA objective into the sample space.



Sample Chamber

Designed to accommodate a variety of configurations with incredible sample, electrical, and optical access for total experiment flexibility; simply lift off the vacuum housing assembly and radiation shield for unobstructed access to the sample and wiring. Six standard side panels support a wide range of RF, DC, fiber-optic or gas feedthroughs. Three large side panels support high density electrical connections.


Configurable optical cryostat for demanding applications in quantum

| Dimensions | |
|--|---|
| Sample Space Standard configuration, customization available | Ø200 mm x 116 mm |
| Performance | |
| Temperature Platform temperature | 3.6 K – 50 K |
| Temperature stability (P-P) With damped manual positioner | <20 mK |
| Vibrations (P-P) | <30 nm |
| Cool Down Time to 4.2K Depending on lab and sample environment | 6 Hours |
| Cooling Power at 4.2K | >250 mW |
| Optical Access | |
| Optical Windows Standard configuration, customization available | 7 Side + 1 Top |
| Beam Height | 137 mm |
| Acceptance Angle (Full) Top Window, Standard Sample Height | 113° |
| Electrical Access | |
| Electrical | 24 DC |
| Configurable Side Panels | 6 |
| Control | |
| Temperature Control Channels | 2 |
| Remote Control and Scripting | V MAGAIN |
| Cryo-Cooler | |
| Compressor | Water-cooled |
| Cold Head | Pulse tube |
| Flex Lines | 20 meters |
| Options | |
| Sample Mounts | Multiple (Including electrical and custom designs) |
| Variable Temperature | ATSM (4.2K-350K) |
| Optical | Cryo-Optic (horizontal) Window Substrate Low Working Distance |
| Vacuum | Turbo |
| Positioning | Manual Positioner The Rook Nanopositioner 3 rd Party Nanopositioners |
| Interfacing (Side Panel Feedthroughs) | RF, DC, Fiber, Gas, Vacuum |




Configurable optical cryostat for demanding applications in quantum

Dimensions



Top-down view



[346.5] 13.6 [614.5] 24.2 [279.4] 11.0

Profile

Side view